


Wywietrzak dachowy cyldryczny (kVA)



Sposób zamawiania:

- » Typ wywietrzaka **kVA**
- » Wymiar **d**
- » Materiał **OC, KO**

- ❖ rodzaj blachy: blacha ocynkowana, blacha kwasoodporna,
- ❖ element zakończony jest gładko (na wsuwkę) do d=315 mm, a większe średnice pierścieniem KKOP

Średnica nominalna d (mm)	d ₁ (mm)	h ₁ (mm)	h (mm)	Masa wywietrzaka kVA (kg)
100	260	160	285	1,67
125	290	170	325	2,43
160	320	192	372	3,52
180	360	215	410	4,34
200	400	252	455	5,39
225	450	270	490	6,68
250	500	300	525	8,11
280	560	335	600	10,01
315	630	390	700	12,48
355	710	425	750	16,49
400	800	480	880	20,66
450	900	540	950	27,53
500	1000	580	1000	34,51
560	1120	670	1130	42,90
630	1260	760	1270	53,85
710	1420	850	1400	67,88
800	1600	960	1550	85,61
900	1800	1080	1750	140,46
1000	2000	1200	1950	173,73
1120	2240	1345	2150	236,96
1250	2400	1500	2350	294,03

Wielkość d (mm)	Prędkość wiatru (m/s)								
	1,0	1,5	2,0	2,5	3,0	3,5	4,0	5,0	6,0
	Wydajność powietrza dla najbardziej popularnych wymiarów (m ³ /h)								
100	14	21	28	35	42	49	55	70	84
160	35	52	70	87	105	122	140	175	210
200	55	82	110	135	165	190	220	270	325
250	85	127	170	212	254	296	340	425	510
315	123	185	245	308	370	430	480	620	740
400	215	325	435	545	655	760	870	1090	1310
500	340	510	610	860	1020	1280	1360	1700	2050
630	510	750	1020	1260	1490	1750	2020	2510	2980
1000	1360	2040	2720	3400	4080	4760	5440	6800	8160